

Interior-Flex

May 2010

1 Product Description

Muralplast Interior-Flex is a matt emulsion paint designed for application to interior walls and ceilings.



2 Properties

- Can be applied to interior walls and ceilings
- Bridges hairline cracks
- Flexes to accommodate movement in substrate to prevent cracking that would otherwise occur with conventional matt emulsion
- Water-based non-hazardous
- · Attractive matt finish
- Low odour
- Excellent coverage
- Wipeable when dry
- Can be applied by brush, roller or spray
- 5 litres covers approximately 50 m² per coat depending on substrate texture, porosity and application method
- Touch dry in 2 hours, recoatable after 4 hours at 18°C 65% relative humidity
- Available in 2.5 and 5 litre cans
- Colours: Brilliant White, Magnolia and other colours subject to minimum order quantity

3 Preparation

- Ensure all surfaces are free from oil, grease, dirt, dust and loose particles
- Remove all loose and flaking paint on existing painted surfaces and rub down with abrasive paper where necessary
- Large cracks or voids should be filled with flexible filler
- Areas affected by mould should be treated with a suitable fungicidal wash
- On plasterboard or any porous substrate the first coat should the first coat should be thinned with approximately 30% clean water

4 Application

- Stir thoroughly, check colour before use
- Apply by brush, roller or spray
- Do not apply at temperatures below 8 °C
- After preparation, brush neat Interior-Flex into hairline cracks and allow to dry. Then apply one or two full coats over the whole area as required.





Interior-Flex

5 Storage

Keep out of reach of children. Protect from frost. Do not store at low temperatures or by hanging on a hook

6 Clean Up

Clean tools and equipment with water immediately after use

7 Health & Safety

Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed. No special protective clothing or skin protection is required under normal conditions of use. If there is a real risk of splashing, wear protective goggles. If swallowed do not induce vomiting - contact a doctor or a specialist. Keep out of the reach of children

Technical Assistance

For technical advice and assistance please contact the Muralplast Technical Office on the number below.

Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the Material Safety Data Sheet.

