

## 1 Product Description

Muralplast Extra-Flex is a flexible exterior masonry paint designed for the protection of exterior masonry, roughcast, pebble-dash, brickwork, cement and concrete rendered surfaces.



## 2 Properties

- Can be applied to exterior masonry, roughcast, pebble-dash, brickwork, cement and concrete rendered surfaces
- Bridges hairline cracks
- Flexes up to 400% to accommodate movement in substrate to prevent cracking that would otherwise occur with conventional masonry paint
- Water-based non-hazardous
- Attractive smooth satin finish
- Quick drying
- Long lasting
- Can be applied by brush, roller or spray (use HVLP or airless spray for best results)
- 5 litres covers approximately 50 m<sup>2</sup> per coat depending on substrate texture, porosity and application method
- Touch dry in 2 hours, recoatable after 4 hours at 18°C 65% relative humidity
- Available in 5 litre cans
- Colours: Brilliant White, Black, Old White, Suffolk Pink, Cream, Sandstone, Portland Stone, Parchment, Buttermilk, Gardenia, Magnolia and other colours subject to minimum order quantity

## 3 Preparation

- Ensure all surfaces are free from oil, grease, dirt, dust and loose particles
- Remove all loose and flaking paint on existing painted surfaces and rub down with abrasive paper where necessary
- Areas affected by mould, lichen algae or moss should be treated with a suitable fungicidal wash
- On untreated, new cement, render or any porous substrate the first coat should be thinned with approximately 30% clean water

## 4 Application

- Stir thoroughly, check colour before use
- Apply by brush, roller or spray
- Do not apply at temperatures below 10 °C or when foggy or likely to rain before the paint has dried
- Apply at least two full coats for maximum protection

## 5 Storage

Keep out of reach of children. Do not store by hanging on a hook

## 6 Clean Up

Clean tools and equipment with water immediately after use

## 7 Health & Safety

Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed. No special protective clothing or skin protection is required under normal conditions of use. If there is a real risk of splashing, wear protective goggles. If swallowed do not induce vomiting - contact a doctor or a specialist. Keep out of the reach of children

### Technical Assistance

For technical advice and assistance please contact the Muralplast Technical Office on the number below.

### Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the Material Safety Data Sheet.