

1 Product Description

A water-based tinted translucent sealer for dust proofing concrete, blockwork and brickwork.



2 Properties

- Can be applied to plant areas, lift shafts, ceiling voids
- Seals surface and prevents dusting
- Non-hazardous and non-toxic
- Solvent and silicone-free
- Ready to use
- For airless spray application
- Non-flammable
- Drying time: 6 - 8 hours depending on temperature
- Coverage 15-20m² litre per coat - usually applied in one coat
- Available in 20 litre containers
- Colours - clear or pigmented

3 Preparation

- Surfaces should be sound and dry and free from oil, wax and grease

4 Application

- Shake the container well before use
- Use directly from the container; do not dilute
- Apply using an airless spray
- Do not apply when the temperature of the surfaces to be treated is below 5°C

5 Storage

Keep out of reach of children.
Protect from frost.

6 Clean Up

Clean tools and equipment immediately after use with water.

7 Health & Safety

Ensure adequate ventilation during application and drying. Keep out of reach of children. In case of contact with eyes, rinse immediately with clean water. After contact with skin, wash off immediately with soap and water or a recognised skin cleaner. Contains no added lead.

Technical Assistance

For technical advice and assistance please contact the **Muralplast Technical Office** on the number below.

Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the Material Safety Data Sheet.