

## 1 Product Description

A flexible, elastic coating, that can be quickly applied to form a high-build, seamless skin.



## 2 Properties

- For internal and external use for encapsulating or waterproofing
- Suitable for use on most surfaces including roofing tiles, slate brick, concrete, corrugated iron, galvanised sheeting, asbestos, asphalt, felt, copper, zinc and timber
- Ready to use
- Drying time: 1 - 3 hours at 18°C and 65% humidity
- Coverage on smooth surfaces approximately 6 - 8m<sup>2</sup> per litre
- Available in 20 litre containers
- Colours - BS 4800 and RAL

## 3 Preparation

- Surfaces should be sound and dry and free from oil, wax and grease, dust and loose particles

## 4 Application

- Stir thoroughly and check colour before use
- Apply preferably using an airless spray. Can be applied by brush or roller

## 5 Storage

Keep out of reach of children.  
Protect from frost.

## 6 Clean Up

Clean tools and equipment immediately after use with clean, warm, soapy water.

## 7 Health & Safety

Ensure adequate ventilation during application and drying. Keep out of reach of children. In case of contact with eyes, rinse immediately with clean water. After contact with skin, wash off immediately with soap and water or a recognised skin cleaner. Contains no added lead.

### Technical Assistance

For technical advice and assistance please contact the **Muralplast Technical Office** on the number below.

### Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the Material Safety Data Sheet.