

1 Product Description

A self-priming, quartz-based, breathable coating that can be applied to a damp substrate allowing moisture to pass through its film.



2 Properties

- Suitable for the decoration of most building surfaces
- Ideal for bare masonry surfaces such as brick, block, render and concrete
- Can be used both internally and externally
- Offers excellent weather protection
- Drying time: 1 - 3 hours at 18°C and 65% humidity
- On smooth surfaces a 20kg drum will cover approx. 18 - 20 m² for the two coat process
- Available in 20kg containers
- 8 standard colours. Special colours on request for minimum orders of 20 drums

3 Preparation

- Surfaces should be sound and dry and free from oil, wax and grease, dust and loose particles. Ferrous metals should be primed with the appropriate metal primer.

4 Preparation

- Stir thoroughly and check colour before use
- Add clean water as appropriate for applying base coat. Allow to dry and apply a second coat using special Muralplast textured rollers

5 Storage

Keep out of reach of children.

Protect from frost.

6 Clean Up

Clean tools and equipment immediately after use with clean, warm, soapy water.

7 Health & Safety

Ensure adequate ventilation during application and drying. Keep out of reach of children. In case of contact with eyes, rinse immediately with clean water. After contact with skin, wash off immediately with soap and water or a recognised skin cleaner. Contains no added lead.

Technical Assistance

For technical advice and assistance please contact the **Muralplast Technical Office** on the number below.

Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the **Material Safety Data Sheet**.